

CAPICORDA PREISOLATI 0,25÷6 mm² PRE-INSULATED TERMINALS 0,25÷6 mm²

EAC CE



FORCELLE CON ZIGRINATURA ANTISCIVOLO

La zigrinatura antiscivolo consente una migliore tenuta sulla vite, rendendo il prodotto più sicuro e più facile da utilizzare.

FORK TERMINALS WITH ANTI SLIP GROOVES

The anti slip grooves provide a better connection on the screw, thus increasing its functionality and safety.

MATERIALE

Rame elettrolitico 99,9 stagnato
Tubetto PVC autoestinguente


TUTTI I CAPICORDA POSSONO ESSERE FORNITI CON BUSSOLA ANTIVIBRANTE IN RAME CHE ASSICURA UNA DOPPIA CONNESSIONE SUL COLLETTO ATTACCATO AL CAVO. AGGIUNGERE -BA DOPO IL CODICE ARTICOLO (ES. A2/P-BA)

MATERIAL




99,9 tinned electrolytic copper
Self extinguishing PVC

ALL TERMINALS CAN BE SUPPLIED WITH A SPECIAL ANTI VIBRATION COPPER SLEEVE TO GUARANTEE A DOUBLE CONNECTION ON THE COLLAR ATTACHED TO THE CABLE. ADD -BA AFTER THE ITEM CODE (ES. A2/P-BA)

CAPICORDA A FORCELLA / FORK TERMINALS



PRODOTTI INNOVATIVI INNOVATIVE PRODUCTS

B135L/P 	Forcella colletto lungo Fork terminal with long neck
A135S/P 	Forcella con blocco tipo "S" Locking fork terminals "S" type
B14L/P B16L/P 	Forcella cava lunga per ponte Long quarry fork terminal

ARTICOLO ARTICLE	COLORE COLOUR	SEZIONE WIRE RANGE mm ²	AWG	Ø A FORO VITE SCREW HOLE	B	C	L	PEZZI PER CONFEZ. PCS PER PACK.	BLISTER con codice a barre with barcode
A13/P	Red	0,25÷1,5	22÷16	3	5	1,8	20	1000	100
A135/P		0,25÷1,5	22÷16	3,5	5,9	1,8	18,5	1000	100
A135G/P		0,25÷1,5	22÷16	3,5	7,8	1,8	19,5	1000	100
A135S/P		0,25÷1,5	22÷16	3,5	6,5	1,8	19	1000	100
A14/P		0,25÷1,5	22÷16	4,1	6,5	1,8	20	1000	100
A15/P		0,25÷1,5	22÷16	5,2	8,5	1,8	20	1000	100
A16/P		0,25÷1,5	22÷16	6,2	10,5	1,8	21,5	1000	100
A18/P		0,25÷1,5	22÷16	8,2	12	1,8	27	1000	100
B13/P	Blue	1,5÷2,5	16÷14	3	5,5	2,4	20,5	1000	100
B135/P		1,5÷2,5	16÷14	3,5	6,3	2,4	20,5	1000	100
B135G/P		1,5÷2,5	16÷14	3,5	6	2,4	23,5	1000	100
B135L/P		1,5÷2,5	16÷14	3,5	6,3	2,4	24	1000	100
B14/P		1,5÷2,5	16÷14	4,1	6,5	2,4	20,4	1000	100
B14L/P		1,5÷2,5	16÷14	4,1	6,5	2,4	21,4	1000	100
B14S/P		1,5÷2,5	16÷14	4,1	6,5	2,4	21	1000	100
B15/P		1,5÷2,5	16÷14	5,2	9	2,4	22	1000	100
B16/P		1,5÷2,5	16÷14	6,2	10,5	2,4	24	1000	100
B16L/P		1,5÷2,5	16÷14	6,2	10,5	2,4	25	1000	100
B18/P		1,5÷2,5	16÷14	8,2	12	2,4	27	1000	100
B110/P		1,5÷2,5	16÷14	10,2	13,5	2,4	28	1000	50
B112/P	1,5÷2,5	16÷14	12,2	18	2,4	35	1000	50	
C13/P	Yellow	2,5÷6	12÷10	3,5	6,9	3,6	26	500	50
C14/P		2,5÷6	12÷10	4,3	8	3,6	27	500	50
C14S/P		2,5÷6	12÷10	4,1	8	3,6	24	500	50
C15/P		2,5÷6	12÷10	5,2	10,5	3,6	28	500	50
C16/P		2,5÷6	12÷10	6,4	11,5	3,6	30	500	50
C18/P		2,5÷6	12÷10	8,5	13	3,6	31	500	50
C110/P		2,5÷6	12÷10	10,5	15	3,6	31	500	50
C112/P		2,5÷6	12÷10	12,2	18	3,6	38	500	50

PINZE CONSIGLIATE PER LA CRIMPATURA DEI TERMINALI PREISOLATI PER SEZIONI DA 0,25 A 6 mm² TOOLS SUGGESTED FOR CRIMPING PRE INSULATED TERMINALS WIRE RANGE FROM 0,25 TO 6 mm²



ART. 60

Pinza a cricchetto per preisolati 0,25 a 6mm². Doppia aggraffatura + punzone controllo qualità.
Ratchet tool for insulated terminals 0,25 to 6 mm². Double crimping + quality control punch.



ART. 54

Pinza per capicorda preisolati doppia aggraffatura da 0,25 a 6 mm². Taglia e spella fili.
Tool for insulated terminals double crimping from 0,25 up to 6 mm². Cut and wire stripper.



ART. 53

Pinza per capicorda nudi e preisolati da 0,25 a 6 mm².
Tool for insulated and not insulated terminals from 0,25 up to 6 mm².